

Wastewater

MODELS

Order Number	HP	Phase	Volts	RPM	Impeller Diameter (in.)	Maximum Amps	Locked Rotor Amps	KVA Code	Full Load Efficiency %	Resistance		Power Cable Size	Weight (lbs.)
										Start	Line-Line		
WE0311L	0.33	1	115	1750	5.38	10.7	30.0	M	54	11.9	1.7	16/3	56
WE0318L			208			6.8	19.5	K	51	9.1	4.2		
WE0312L			230			4.9	14.1	L	53	14.5	8.0		
WE0311M			115			10.7	30.0	M	54	11.9	1.7		
WE0318M			208			6.8	19.5	K	51	9.1	4.2		
WE0312M			230			4.9	14.1	L	53	14.5	8.0		
WE0511H	0.5	1	115	3450	3.56	14.5	46.0	M	54	7.5	1.0	14/3	60
WE0518H			208			8.1	31.0	K	68	9.7	2.4	16/3	60
WE0512H			230			7.3	34.5	M	53	9.6	4.0	16/3	60
WE0538H		3	200			4.9	22.6	R	68	NA	3.8	14/4	60
WE0532H			230			3.3	18.8	R	70	NA	5.8		
WE0534H			460			1.7	9.4	R	70	NA	23.2		
WE0537H		575	1.4		7.5	R	62	NA	35.3	35.3	14/4	60	
WE0511HH		1	115		14.5	46.0	M	54	7.5	1.0	14/3	60	
WE0518HH			208		8.1	31.0	K	68	9.7	2.4	16/3	60	
WE0512HH			230		7.3	34.5	M	53	9.6	4.0	16/3	60	
WE0538HH			3		200	4.9	22.6	R	68	NA	3.8	14/4	60
WE0532HH					230	3.6	18.8	R	70	NA	5.8		
WE0534HH	460			1.8	9.4	R	70	NA	23.2				
WE0537HH	575	1.5	7.5	R	62	NA	35.3	35.3	14/4	60			
WE0718H	0.75	1	208	3450	4.06	11.0	31.0	K	68	9.7	2.4	14/3	70
WE0712H			230			10.0	27.5	J	65	12.2	2.7	14/3	70
WE0738H		3	200			6.2	20.6	L	64	NA	5.7	14/4	70
WE0732H			230			5.4	15.7	K	68	NA	8.6		
WE0734H			460			2.7	7.9	K	68	NA	34.2		
WE0737H			575			2.2	9.9	L	78	NA	26.5		
WE1018H	1	1	208	3450	4.44	14.0	59.0	K	68	9.3	1.1	14/3	70
WE1012H			230			12.5	36.2	J	69	10.3	2.1	14/3	70
WE1038H		3	200			8.1	37.6	M	77	NA	2.7	14/4	70
WE1032H			230			7.0	24.1	L	79	NA	4.1		
WE1034H			460			3.5	12.1	L	79	NA	16.2		
WE1037H			575			2.8	9.9	L	78	NA	26.5		
WE1518H	1.5	1	208	3450	4.56	17.5	59.0	K	68	9.3	1.1	14/3	80
WE1512H			230			15.7	50.0	H	68	11.3	1.6	14/3	80
WE1538H			200			10.6	40.6	K	79	NA	1.9	14/4	80
WE1532H		3	230			9.2	31.7	K	78	NA	2.9		
WE1534H			460			4.6	15.9	K	78	NA	11.4		
WE1537H			575			3.7	13.1	K	75	NA	16.9	16.9	14/4
WE1518HH		1	208		17.5	59.0	K	68	9.3	1.1	14/3	80	
WE1512HH			230		15.7	50.0	H	68	11.3	1.6	14/3	80	
WE1538HH			3		200	10.6	40.6	K	79	NA	1.9	14/4	80
WE1532HH					230	9.2	31.7	K	78	NA	2.9		
WE1534HH					460	4.6	15.9	K	78	NA	11.4		
WE1537HH			575		3.7	13.1	K	75	NA	16.9	16.9	14/4	80
WE2012H	2	1	230	3450	5.38	18.0	49.6	F	78	3.2	1.2	14/3	83
WE2038H			200			12.0	42.4	K	78	NA	1.7	14/4	83
WE2032H		3	230			11.6	42.4	K	78	NA	1.7		
WE2034H			460			5.8	21.2	K	78	NA	6.6		
WE2037H			575			4.7	16.3	L	78	NA	10.5		